Republic of the Philippines OVERSEAS WORKERS WELFARE ADMINISTRATION

OWWA Center Bldg., F.B. Harrison St., Cor. 7th St., Pasay City Tel# 833-0113 Telefax# 833-1010

> P.R. No. 2023-06-0071 DATE: 19-Jun-23

REQUEST FOR QUOTATION / PROPOSAL

COMPANY NAME:

ADDRESS OF COMPANY:

To whom it may concern:

Please quote your lowest price/s (taxes included) on the lot or item/s below, subject to the General Conditions indicated herein, stating the shortest time of delivery and submit your quotation using your company letterhead or this form duly signed by your official representative to Overseas Workers Welfare Administration, Third Floor OWWA Center Building, 7th Street corner, FB Harrison, Pasay City not later than 26 June 2023, 10:00 a.m.

MARIAN GABRIEUE F. PIZARRA

Supply Officer

M. Satchahan

Engr. GERARDO S. GATCHALIAN

OIC, PPMD

PROJECT	TITLE/NAME: Proposal for the Supply and Delivery of Vario	us Machin	ery and Eq	uipment	DEALER'S/SUPPLIER'S OFFER	
ITEM NO.	SPECIFICATIONS	QTY	UNIT	APPROVED BUDGET PER LINE ITEM (ABC)	UNIT COST (Vat inclusive)	TOTAL COST (Vat inclusive)
	Supply and Delivery of Various Machinery and Equipment					
1.	Ear Muff, Over-the-head	5	pcs	2,870.00		
2.	Gas Mask	4	pcs	1,700.00		
3.	Hard Hat	24	pcs	750.00		
4.	Full Protection Arrester, Double Lanyard	6	pcs	5,000.00		
5.	Torch Lights/Flashlights	8	pcs	1,500.00		
6.	Worklights Stand, Dual Head, Double Head Light	2	pcs	5,000.00		
7.	Rotary Hammer Drill	1	рс	7,000.00		
8.	Bolt Cutter, Heavy Duty 18", 450mm-5/16" cutting capacity	1	рс	9,000.00		
9.	Clamp Meter	2	pcs	14,000.00		
10.	Cordless Impact Drill	2	pcs	9,000.00		
11.	Cordless Screwdriver	2	pcs	5,000.00		
12.	Orbit Sander	2	pcs	5,000.00		
13.	Angular Sander	2	pcs	5,600.00		
14.	Belt Sander	1	рс	10,000.00		
15.	Electric Router	1	рс	5,000.00		
16.	Air Blower 230V	1	рс	3,000.00		
17.	Cut-off Machine 15"/16", 200W, 230V	1	рс	8,500.00		
18.	Angel Grinder 4" (100mm), 230V/60Hz	2	pcs	5,500.00		
19.	ACU Vaccum Pump	1	рс	8,000.00		
20.	PPR Tube Fusion Machine	2	pcs	3,000.00		
21.	Portable Pressure Washer	2	pcs	3,000.00		
22.	Cordless Impact Wrench	1	рс	14,500.00		
23.	Jack Stand, 6 tons	1	рс	2,500.00		
24.	Cross Wrench 16"	1	рс	1,500.00		
25.	Pneumatic Grease Gun	1	рс	2,500.00		
26.	Cordless Work Lamp	1	рс	2,500.00		
27.	Booster Cable with Light 600A	1	рс	2,500.00		

Additional Documentary Requirements must be submitted upon submission of offer:		
PhilGEPS Certificate or PhilGEPS Registration Number		
2. Mayor's / Business Permit		
Please take note that the Omnibus Sworn Statement shall be submitted within 5 days upon acceptance of Notice of Award.		
Note: Bidders may also submit their bid proposal and supporting documents through email address: procurement@owwa.gov.ph		

GENERAL CONDITIONS

- 1. Entries must be typewritten / if handwritten, it must be clear and legible;
- 2. Bidders must submit certificate of PHILGEPS Registration;
- 3. Bidders must submit necessary business permits (SEC, LGU, DTI, CDA, etc.);
- 4. All quotation can be submitted through the following means: a) in a SEALED ENVELOPE, or b) thru ELECTRONIC MAIL, or c) FACSIMILE. Label the envelope with the following:

Bidder's Company Name

PHILGEPS Reference No.

Project Title/Name

PR No.

- 5. Item/s delivered must have warranties for unit replacements, parts, labor or other services;
- 6. Quoted prices must be inclusive of taxes and shall not exceed the Approved Budget for the Contract (ABC);
- Proposal/Quotation submitted without signature of the authorized signatory shall not be accepted;
- 8. Proposal/Bid modifications submitted beyond the scheduled deadline shall not be considered;
- 9. Price quoted/ submitted on the deadline shall be considered as final and unalterable;
- 10. Use of non-discretionary/non-discriminatory selection criteria as tie-breaking method in case of two or more bidders determined and declared as the Lowest Calculated and Responsive Bidder (LCRB) in accordance with GPPB Circular No. 06-2005;
- 11. The OWWA reserves the right to accept or reject any bid, to annul the bidding process, and to reject at any time prior to contract award, without thereby incurring any liability to the affected bidder or bidders.

 $\frac{1}{1}$

Page 2 of 2

DELIVERY: 30	calendar	days	upon	receipt	of	PO/NTF

TERMS OF PAYMENT: Government Terms

PRICE VALIDITY: 60 days from date of quotation/proposal

Сотр	any Name
	ignature of Authorized esentative
Des	ignation
Company Te	el./Fax/Mobile No.

TECHNICAL SPECIFICATIONS (VARIOUS MACHINERY AND EQUIPMENT)

Item No.	Qty	Unit Measure	Item Description .	Estimate Unit Cost	Estimate Total Cost
1	5	pcs	EAR MUFF, OVER-THE HEAD Stainless steel headband distributes weight for low pressure fit Earcup pivot points tilt for comfort that adjusts to individual wearers Noise Reduction Rating (NRR) 25 decibels Color: Yellow Application: Assembly, Facility maintenance, demolition, grinding, electrical, machine operation, sanding, etc.	2,870.00/pc	14,350.00
2	4	pcs	GAS MASK Dual Filter, Application: Paint Preparation, UV Protection, Assembly & Mechanical, Welding, Painting, Sawing, Cleaning, Chemical Handling, Full Face	1,700.00/pc	6,800.00
3	24	pcs	 HARD HAT Type I - Class C Hard Hats with Chin Strap White HDPE Shell Material Ratchet Type Adjustment Safety Orange – 15 pcs / White – 9 pcs 	750.00/pc	18,000.00
4	6	pcs	 FULL PROTECTION ARRESTER, DOUBLE LANYARD Set of seat made of Polyester fiber material, the connecting and locking are made of stainless steel. Attach a D-lock hook on the back. Strap at comfortable sitting position. Adjustable straps in the thigh, chest and abdomen to feel comfortable & comfortable for the user. Combined with the suspension hook 1 hook to, made of Polyamide fiber material, the lock is made of stainless-steel metal. The static force wire is 22 kN and the dynamic force is 6 kN. Double safety belt with shock absorber. The structure consists of a fixed wire to the shock; one end is the key H-3101 with aperture of 53mm. The product clearly shows the parameters such as production standards, production year, production materials, manufacturers. Standard: Safety belts are standard EN361: 2002, CE0321 Suspension belts meet the standard CE 0299, EN355. 	5,000.00/pc	30,000.00
5	8	pcs	TORCH LIGHT/FLASHLIGHTS LED, rechargeable Aviation Grade aluminum alloy: 6N01-T6 Brightness: Max: 400 lumens, Mid: 150 lumens, Low: 50 lumens Use 15650 Li ion Battery High light: 4H Runtime Low light: 18H runtime Four switches: high, middle and low light	1,500.00/pc	12,000.00
6	2	pcs	WORKLIGHTS STAND, DUAL HEAD, DOUBLE HEAD LIGHT Min. height 68 cm Max. height 158 cm LED output: 2x50w. Cable length: 3M. Lumen: Lm. 4000 Ingress protection: IP65. Aluminum die cast body. Tempered glass screen. Telescopic mast. Includes collapsible tripod.	5,000.00/pc	10,000.00
7	1	рс	Powerful 7 AMP motor delivers 2.1 ft. lbs. of impact energy to handle the most demanding applications	7,000.00	7,000.00

			 Anti-Vibration Technology (AVT®) is an internal counterbalance system that greatly reduces vibration by moving a counterweight in the opposite direction of drive piston Integrated damper spring at the base of the impact bolt is engineered to absorb impact vibrations from the drill bit Torque limiting clutch engineered to prevent gear damage by automatically disengaging gears if the bit binds L.E.D. light illuminates drilling surface for more productivity in low light applications Recessed hammer function selector located below gear housing for improved durability Variable speed trigger enables user to match the speed to the application for greater versatility 3-mode operation for various applications with "Rotation Only", "Hammering with Rotation" or "Chipping Only" functions 40-bit angle settings allow the bit to be set at different positions for operating convenience Ergonomic "Pistol-grip" handle with rubberized soft grip for increased comf Bit type; SDS Plus Corded type 220 V 		
8	1	рс	BOLT CUTTER, HEAVY DUTY 18", 450mm-5/16" CUTTING CAPACITY	9,000.00	9,000.00
9	2	pcs	CLAMP METER • AC current Range 40.00 A / 400.0 A • Accuracy 2% ± 5 digits (45 Hz to 65 Hz) 2.5% ± 5 digits (65 Hz to 400 Hz) DC current Range 40.00 A / 400.0 A • Accuracy 2% ± 5 digits • AC voltage Range 600.0 V • Accuracy 1.5% ± 5 digits • DC voltage Range 600.0 V • Accuracy 1.0% ± 5 digits • Resistance Range 400.0 Ω / 4000 Ω / 40.00 kΩ • Accuracy 1.0% ± 5 digits • Continuity ≤ 30 Ω • Capacitance 0 to 100.0 μF / 100μF to 1000 μF • Frequency 5.0 Hz to 500.0 Hz • AC response True-RMS • Backlight Yes	14,000.00/pc	28,000.00
10	2	pcs	CORDLESS IMPACT DRILL Chuck type -1/4" hexagonal Maximum torque - 60 Nm (1); 110 Nm (2); 194 Nm (3) 1 No load RPMgear - 1: 1000 rpm; gear 2: 1500 rpm; gear 3: 2700 rpm Full hammering frequency - 3500 impacts/minute Number of gears -3 A-weighted emission sound pressure level - 87 dB (A) 2 Rated voltage - 21.6 V Applications: Driving self-drilling and self-tapping screws up to 4.8 mm diameter in steel Driving 6 mm diameter HUS screw anchors in masonry and concrete Driving Spax screws up to 8 mm diameter in wood Driving 8 mm and 10 mm HRD frame anchors in masonry and concrete Drilling in wood with WDB-S spade bits Features High-efficiency brushless motor means the tool lasts longer and gets more work done per charge Three gears and electronic speed control for easy switching between different driving speeds Ergonomic grip and trigger for maximum comfort and convenience during long periods of use	9,000.00/pc	18,000.00

			Robust 1/4" hexagonal click-in chuck Four bright LEDs around the chuck provide direct illumination of the work surface		
11	2	pcs	CORDLESS SCREWDRIVER Screwdriver Combo 3.6V 1.5AH Li-ion Cordless Screwdriver Combo Kit LED job light for bright illumination of the work piece, makes locating the screw easier Forward and reverse switch, two button switches located on the grip of the screwdriver turn the motor in forward or reverse Powered by 3.6V / 1.5Ah Built in battery charged through micro USB connector port and the bottom of the grip Lamp switch LED lamp can manually be turned on and off from the switch located at the base of the grip Straight or pistol grip style screwdriver easily folds and locks into either straight or pistol grip position. Voltage: 3.6V Battery type: In-built Li-ion No load speed: 220rpm Driving shank: 1/4" Hex Max fastening torque: 4Nm Max capacity (wood screw): Ø3.8mm x 32mm Noise K: 3dB(A) 1 x 1.5Ah Battery in-built 1 x AC adaptor 81 x Drill bit pieces 1 x Carry case	5,000.00/pc	10,000.00
12	2	pcs	ORBIT SANDER Rated input power - 250 W Sanding pad diameter- 125 mm Oscillating circuit diameter - 2.5 mm No-load speed- 7,500 – 12,000 rpm Orbital stroke rate- 15,000 – 24,000 opm	5,000.00/pc	10,000.00
13	2	pcs	Sanding sheet / disc attachment- hook-and-loop fastening ANGULAR SANDER Voltage:220-240V~50/60Hz Input power:240W No-load speed:14000rpm	5,600.00/pc	11,200.00
14	1	рс	BELT SANDER Abrasive Belt Size 100 mm x 610 mm Belt Speed 210 to 440 m/min (var) Corded Dust Collection Dust Bag Supplied Motor Power 1,010 W Rating Trade/Professional Voltage 230 V	10,000.00	10,000.00
15	1	рс	ELECTRIC ROUTER O" - 1-3/8" plunge depth capacity for easy penetration into work piece Plunge depth adjustment lever with 3 pre-set depth stops for added precision Oversized ball bearing construction for longer tool life Durable flat top design for added convenience when changing bits Rubberized contoured handles with built-in switch for better fit and control Chip deflector engineered to direct chips away from the operator Easy-to-read depth scales Powerful 8.0 AMP motor delivers 27,000 RPM for smooth routing Uses 1/4" shank router bits Double insulated	5,000.00	5,000.00
16	1	рс	AIR BLOWER • 230V	3,000.00	3,000.00
17	1	рс	CUT-OFF MACHINE 15"/16" • 200W, 230V	8,500.00	8,500.00
18	2	pcs	ANGEL GRINDER 4" • 100mm	5,500.00	11,000.00

			• 230V/60Hz		
19	1	рс	ACU VACUUM PUMP 4 VALVE R134A R410A & R22 Manifold Gauges A/C Tester Freon gas Service Diagnostic AC W/4 HOSES AC A/C Manifold Gauge Set, Aluminum housing, includes 3 color-coded 60" long service hose + 1black 60" hose Works for R410, R22, R134a, BLACK HOSE Burst pressure: 4000PSI, BLACK HOSE Max working pressure 800PSI, Extra-large sight glass Celsius Degree (C) Reading, Quick disconnect couplers for high/low fittings included Each coupler have a shut off valve to prevent loss of refrigerant Blue Gauge (low): 2-1/2" diameter, Red Gauge (high): 2-1/2" diameter, Red and Blue 60" long charging hose R12, R22, R134A x 60 " with knurled fittings SAE (1/4" FFL x 60 " with knurled fittings) (3000PSI 600PSI)	8,000.00	8,000.00
20	2	pcs	PPR TUBE FUSION MACHINE Body Aluminum Body Heat Element Double heating elements with thermostat Heating elements are made of non-corrosive material Power (W) 1500 watt Temperature Range 50 - 300 °C Welding Diameter 16 - 63 mm Voltage 220 - 240 - Volt 50 - 60 Hz Foot: Aluminum Foot Warranty: 1 Year Set Dimensions 440 mm x 270 mm x 100 mm Set Include Welding Machine, Aluminum Yoke Foot, Cutter, Allen Key Steel Tape, Swiss Teflon Coated Die Plates (20 mm, 25 mm, 32 mm, 40 mm)	3,000.00/pc	6,000.00
21	2	pcs	PORTABLE PRESSURE WASHER Voltage: 220-240 V Frequency: 50/60 Hz Rated Power: 1,200 W Rated Pressure: 70 bar Maximum Pressure: 100 bar Rated Flow: 5.5 L/min	3,000.00/pc	6,000.00
22	1	рс	CORDLESS IMPACT WRENCH Specifications Battery chemistry XR Li-lon Voltage 18 V Battery Capacity 4.0 Ah Max. Torque 203 Nm	14,500.00	14,500.00
			Power Output 250 Watt		
23	1	DC		2.500.00	2.500.00
23	1 1	pc	JACK STAND, 6 tons	2,500.00 1.500.00	
24	1	рс	JACK STAND, 6 tons CROSS WRENCH 16"	1,500.00	1,500.00
			JACK STAND, 6 tons		



JUAN M. PARCO, JR. OIC, EGSD / Provisional Member