

**Republic of the Philippines**  
**OVERSEAS WORKERS WELFARE ADMINISTRATION**  
 OWWA Center Bldg., F.B. Harrison St., Cor. 7th St., Pasay City  
 Tel# 833-0113 Telefax# 833-1010

P.R. No. 2024-02-0011  
 DATE: 13-Feb-24

**REQUEST FOR QUOTATION / PROPOSAL**


COMPANY NAME:

ADDRESS OF COMPANY:

To whom it may concern:

Please quote your lowest price/s (taxes included) on the lot or item/s below, subject to the General Conditions indicated herein, stating the shortest time of delivery and submit your quotation using your company letterhead or this form duly signed by your official representative to Overseas Workers Welfare Administration, Third Floor OWWA Center Building, 7th Street corner, FB Harrison, Pasay City not later than **20 February 2024, 10:00 a.m.**

  
**MARIAM GABRIELLE F. PIZARRA**  
 Supply Officer

  
**Engr. GERARDO S. GATCHALIAN**  
 OIC, PPMD

PROJECT TITLE/NAME: Proposal for One (1) Lot - Supply and Delivery of DSLR Camera and Accessories					DEALER'S/SUPPLIER'S OFFER	
ITEM NO.	SPECIFICATIONS	QTY	UNIT	APPROVED BUDGET FOR CONTRACT (ABC)	UNIT COST (Vat inclusive)	TOTAL COST (Vat inclusive)
	One (1) Lot - Supply and Delivery of DSLR Camera and Accessories			P 836,000.00		
1.	<b>DSLR Camera</b>	2	sets			
	Max Resolution: 8256 x 5504					
	Sensor photo detectors: 47 megapixels					
	Sensor size: Full frame (35.9 x 23.9 mm)					
	ISO: Auto, 64-25600 (expands to 32-102400)					
	Storage types: SD/SDHC/SDXC (UHS-II supported) + XQD					
	USB: USB 3.0 (5 GBit/sec)					
2.	<b>Speed Light</b>	2	sets			
	Automatic Insulated Gate Bipolar Transistor (IGBT) and series circuitry					
	Use four (4) AA-size batteries of the same brand from any of the following types:					
	1.5 V LR6 (AA-size) alkaline batteries					
	1.2 V HR6 (AA-size) rechargeable Ni-MH batteries					
	Flash duration					
	Approx. 1/980 sec. at full output					
	Bounce capability					
	Flash head tilts down to 7° or up to 90° with click-stops at -7°, 0°, 45°, 60°, 75°, 90°					
	Flash head rotates horizontally 180° to the left and right with click-stops at 0°, 30°, 60°, 75°, 90°, 120°, 150°, 180°					
3.	<b>Lens</b>	2	sets			
	<b>Coverage</b>					
	35mm film, FX and DX					
	<b>Focal Length</b>					
	28-300mm. F/3.5-5g ED VR					
	<b>Size</b>					
	3.26" (83mm) diameter by 4.5" (114.5mm) extension from flange					

