

Republic of the Philippines  
**OVERSEAS WORKERS WELFARE ADMINISTRATION**  
 OWWA Center Bldg., F.B. Harrison St., Cor. 7th St., Pasay City  
 Tel# 833-0113 Telefax# 833-1010

P.R. No. 2024-05-0065  
 DATE: 24-May-24


**REQUEST FOR QUOTATION / PROPOSAL**

COMPANY NAME:

ADDRESS OF COMPANY:

To whom it may concern:

Please quote your lowest price/s (taxes included) on the lot or item/s below, subject to the General Conditions indicated herein, stating the shortest time of delivery and submit your quotation using your company letterhead or this form duly signed by your official representative to Overseas Workers Welfare Administration, Third Floor OWWA Center Building, 7th Street corner, FB Harrison, Pasay City not later than **31 May 2024 @ 10:00 a.m.**

  
**Engr. GERARDO S. GATCHALIAN**  
 SAO, PPMD

  
**NIMEFA C. UNICA**  
 OIC, PPMD

PROJECT TITLE/NAME: Proposal for the Supply and Delivery of Various Video and Communication Equipment and Accessories					DEALER'S/SUPPLIER'S OFFER	
ITEM NO.	SPECIFICATIONS	QTY	UNIT	APPROVED BUDGET PER LINE ITEM (ABC)	UNIT COST (Vat inclusive)	TOTAL COST (Vat inclusive)
	<b>Supply and Delivery of Various Video and Communication Equipment and Accessories</b>					
1.	PHONE STABILIZER	2	UNITS	₱ 25,986.00		
				PER UNIT		
2.	DSLR STABILIZER	2	UNITS	₱ 49,998.00		
				PER UNIT		
3.	WIRELESS LAPEL MICROPHONES	3	UNITS	₱ 31,249.00		
				PER UNIT		
4.	WIRELESS EARPHONES WITH MICROPHONES (INTERCOM)	12	UNITS	₱ 12,499.00		
				PER UNIT		
5.	LED VIDEO LIGHT DOUBLE LAMP WITH LIGHTSTAND	1	UNIT	₱ 25,720.00		
				PER UNIT		
6.	HARD TOOL CASE STORAGE BOX FOR CAMERA	3	UNITS	₱ 1,775.00		
				PER UNIT		
7.	HORIZONTAL DRY CABINET BOX FOR CAMERA	1	UNIT	₱ 14,079.00		
	(Please see attached Technical Specifications)					
	<b>Note: Kindly indicate Brand/Model on your bid offer/proposal.</b>					
	<i>At least one (1) year warranty</i>					



**TECHNICAL SPECIFICATIONS  
VARIOUS VIDEO AND COMMUNICATION AND ACCESSORIES**

ITEM NO.	ITEM DESCRIPTION	QUANTITY	AMOUNT	BID OFFER	
				UNIT COST	TOTAL COST
1.	<p style="text-align: center;"><b>PHONE STABILIZER</b></p> <p><b>Dimensions:</b> Unfolded: 276×111.5×99 mm (L×W×H) Folded: 189×84.5×44 mm (L×W×H)  <b>Weight:</b> Gimbal: Approx. 305 g Magnetic Phone Clamp: Approx. 25 g  <b>Compatible Phone Weight:</b> 170-290 g  <b>Compatible Phone Thickness:</b> 6.9-10 mm  <b>Compatible Phone Width:</b> 67-84 mm  <b>Battery Type:</b> Li-Po 2S  <b>Capacity:</b> 1000 mAh  <b>Energy:</b> 7.74 Wh  <b>Charging Temperature:</b> 5° to 40° C (41° to 104° F)  <b>Operating Temperature:</b> 0° to 40° C (32° to 104° F)  <b>Operating Time:</b> Approx. 6 hours and 24 minutes (measured under ideal conditions with the gimbal fully balanced)  <b>Charging Time:</b> Approx. 1 hour 24 minutes (measured with a 10W Type-C charger)  <b>Gimbal Charging Port:</b> USB-C  <b>Mechanical Range</b>  Pan: -161.64° to 173.79°  Roll: -120.30° to 211.97°  Tilt: -101.64° to 78.55°  <b>Max Control Speed:</b> 120°/s  <b>Wireless Mode Model:</b> Bluetooth 5.1  <b>Software App:</b> DJI Mimo  <b>Grip Tripod Dimensions:</b> Length: 138 mm/ Diameter: 32 mm  <b>Weight:</b> Approx. 72 g</p>	2 units	25,986.00 / unit		
2.	<p style="text-align: center;"><b>DSLR STABILIZERS</b></p> <p><b>Accessory Port:</b> NATO Ports, 1/4"-20 Mounting Hole, Cold Shoe, Video Transmission/Focus Motor Port (USB-C), RSS Camera Control Port (USB-C), Focus Motor Port (USB-C)  <b>Battery:</b> Model: BHX711-3000-7.2V, Type: 2S, Capacity: 3000 mAh, Energy: 21 Wh, Max. Runtime: 12 hours <sup>[1]</sup>. Charging Time: Approx. 2.5 hours when using 18W quick charging (supports PD protocol), Suggested Charging Temperature: 5° to 40° C (41° to 104° F)  <b>Connections:</b> Bluetooth 5.0, Charging Port (USB-C)  <b>Ronin App Requirements:</b> iOS 11.0 or above, Android 7.0 or above  <b>Tested Payload:</b> 3 kg (6.6 lbs)  <b>Maximum Controlled Rotation Speed:</b> Pan: 360°/s, Tilt: 360°/s, Roll: 360°/s  <b>Mechanical Range:</b> Pan axis: 360° continuous rotation, Roll axis: -95° to +240°, Tilt axis: -112° to +214°  <b>Operating Frequency:</b> 2.400-2.4835 GHz  <b>Bluetooth Transmitter Power:</b> &lt;8 dBm  <b>Operating Temperature:</b> -20° to 45° C (-4° to 113° F)  <b>Weight:</b> Gimbal: Approx. 990 g (2.18 lbs), Grip: Approx. 200 g (0.44 lbs), Extended Grip/Tripod (Plastic): Approx. 183 g (0.4 lbs), Upper and Lower Quick-Release Plates: Approx. 107 g (0.23 lbs)</p>	2 units	49,998.00 / unit		

	<p><b>Dimensions:</b> Folded: 254×230×68 mm (L×W×H, excluding camera, grip, and the Extended Grip/Tripod), Unfolded: 364×187×170 mm (L×W×H, height includes the grip and excludes the Extended Grip/Tripod)</p> <p><b>Connections:</b> Power/Communication Port (USB-C), HDMI Port (Mini HDMI), RSS Camera Control Port (USB-C)</p> <p><b>Expansion Port:</b> Cold Shoe</p> <p><b>Operating Frequency:</b> 2.400-2.484 GHz, 5.725-5.850 GHz</p> <p><b>Weight:</b> 126 g (0.27 lbs)</p> <p><b>Dimensions:</b> 82×63×24 mm (L×W×H)</p> <p><b>Transmitter Power (EIRP):</b> 2.400-2.4835 GHz: &lt;25 dBm (FCC) &lt;20 dBm (CE/SRRC/MIC) 5.725-5.850 GHz: &lt;25 dBm (FCC/SRRC) &lt;14 dBm (CE)</p> <p><b>Battery:</b> Capacity: 2970 mAh Compatible Charger: 5V/2A Charging Time: Approx. 2.5 hours Max Battery Life: Approx. 3.5 hours</p> <p><b>Transmission Range:</b> 200 m (SRRC/FCC) [2] 100 m (CE) [2]</p> <p><b>Latency:</b> 60 ms</p> <p><b>Operating Current/Voltage:</b> 900 mA, 3.7V</p> <p><b>Operating Temperature:</b> 0° to 45° C (32° to 113° F)</p>				
3.	<p align="center"><b>WIRELESS LAPEL MICROPHONES</b></p> <p>Equivalent Noise Level: 21 dBA Polar pattern: Omnidirectional Transmitter Dimensions: 46.06 x 30.96 x 21.83 mm Receiver Dimensions: 54.20 x 28.36 x 22.49 mm Charging Case Dimensions: 116 x 41.5 x 59.72 mm Transmitter Weight: 28 g Receiver Weight: 28 g Charging Case Weight: 200 g Battery (Charging Case): 18650 Li-ion 3250 mAh Battery (Transmitter): li-ion 360 mAh Battery (Receiver): Li-ion 360 mAh</p> <p><b>Key features:</b> Omnidirectional microphone for clear audio Intelligent noise cancellation for reducing background noise 32-bit float recording for high-quality audio Auto power on and pairing Touchscreen operation Compatible with cameras, smartphones, computers and tablets Up to 6 hours battery life per transmitter/receiver, 18 hours with charging case Magnetic clip-on transmitters for easy attachment</p>	3 units	31,249.00 / unit		
4.	<p><b>WIRELESS EARPHONE S WITH MICROPHONE (INTERCOM)</b></p> <p><b>Headphone</b> Earpiece design: On-ear (Supra-Aural) / Over-Ear (Circumaural) Earpiece Connection / Wearing Style: Headband Number of Earpieces: Single Earpiece (Left or Right Side) Sound Field: Mono Controls/Microphone Location: Controls – Adjustable Boom, Earpiece (Side Unspecified) / Microphone – Earpiece (Side Unspecified) Frequency response: 150 Hz to 7 kHz Total Harmonic Distortion (THD): 1% Maximum Sound Pressure Level (SPL): 115 dB SNR: Headphone: &gt;71 dB Microphone Type: Electret Condenser Mic Boom Location: Interchangeable (Left or Right Side) Pickup pattern: Cardioid (Unidirectional) Noise Cancelling Microphone: yes</p>	12 units	12,499.00 / unit		



	<p>Maximum SPL: 115 dB Distortion: &lt;1%</p> <p><b>Wired Connectivity</b> Audio Connector to Source: None Battery type: Headset: 1 x 26650 Battery Chemistry: Headset: Lithium-ion Capacity (mAh): 700 mAh Runtime: Headset: 10 Hours Operating Temperature: 32 to 113°F / 0 to 45°C Storage Temperature: 14 to 140°F / -10 to 60°C Environmental Protection: None Weight: 6 oz / 170 g (with Batteries)</p> <p><b>System</b> Wireless Technology: Digital DECT (1.9 GHz) DECT Standard: 6.0 Operating Range: 1100' / 335.3 m Wireless Modulation: Analog:GFSK Duplex Mode: Full-Duplex (FDX) Approximate RF Sensitivity: -90 dBm I/O: None</p>				
5.	<p><b>LED VIDEO LIGHT DOUBLE LAMP WITH STAND</b></p> <p><b>AC Power Supply:</b> DC 15V, 6A adapter (AC100-240V 50/60Hz) <b>Channel:</b> 12 <b>Group:</b> 6 Group (A, B, C, D, E, F) <b>Power:</b> 80W <b>Color Temperature:</b> 5600±200K <b>CRI:</b> 96+ <b>R9:</b> 90 <b>TLCI:</b> 95+ <b>Dimming range:</b> Adjustment brightness mode 1%-100%, effect mode 10%-100% <b>Operating temperature:</b> -10 to 50 °C <b>LED beads safety temperature:</b> ≤70°C <b>Size:</b> 173.7x122.5x201mm (without reflector) <b>FL80 Light Brightness:</b> <b>Without reflector:</b> Distance(0.5m): Footcandles (1087.3), 11704lux Distance(1m): Footcandles (278.9), 3002lux Distance(2m): Footcandles (72.8), 784 Distance(3m): Footcandles (36.8), 397  <b>With reflector:</b> Distance(0.5m): Footcandles (7701), 11704lux Distance(1m): Footcandles (1798), 82898lux Distance(2m): Footcandles (335), 16129 Distance(3m): Footcandles (162), 1754  With 2.8m Lightstand – 2 pcs</p>	1 unit	25,720.00		
6.	<p><b>HARD TOOL CASE STORAGE BOX FOR CAMERA</b></p> <p>Material: ABS, Sponge Color: Black Size: 340 x 270 x 100mm</p> <p><b>Features:</b> Excellent shockproof, waterproof, dustproof function Widely used in aviation, outdoor photography, field investigation, scientific exploration and many other fields</p>	3 pcs	1,775.00 / pcs		

	Composite buckle, the use of stretching process, smart, convenient, strong to prevent the collapse of the box Package included: 1 x Box with sponge				
7.	<p align="center"><b>HORIZONTAL DRY CABINET BOX FOR CAMERA</b></p> <p><b>Features and Specifications:</b>  This case for anti-oxidation, anti-deterioration, anti-corrosion, anti-fungus and anti-aging  LED Digital display humidity 25~60%RH  Suitable for cameras, lenses, memory cards, video cameras, telescopes, photographs, slides, CDs, DVDs  Material: 0.8-1.0 thick cold-rolled steel  Have 2 pcs key  Removable steel shelf board and can movable up and down to your need position  Adjustable front feet  Control way: NC control and setting humidity by button,  Tolerance at +/- 1%</p>	1 pc	14,079.00		

**Note: Kindly indicate Brand/Model on your bid offer/proposal.**

PRINT NAME : \_\_\_\_\_

DESIGNATION : \_\_\_\_\_

COMPANY NAME : \_\_\_\_\_

CONTACT DETAILS : \_\_\_\_\_

DATE : \_\_\_\_\_